



Satisfy Professional's Needs

Cordless Impact Driver

TD127D 18V *Li-ion* TD126D 14.4V *Li-ion*

High operation efficiency
with Li-ion battery.



LIGHTER

1.1Ah Lithium-ion Series

Photo:TD127D
Tool does not come with bit.

Max fastening torque:

TD127D - 140N.m **18V Li-ion**

TD126D - 135N.m **14.4V Li-ion**



Photo:TD127D

LED Job light with pre-glow function
On pulling switch trigger, the light automatically turns on before motor starts turning.



Push button type reverse switch

Variable speed control by trigger

- Ergonomically designed handle
- Rubberized soft grip provides comfortable grip and more control while minimizing hand fatigue and pain.


Belt clip (option) can be attached.



Tool does not come with bit.

18V Li-ion


Battery For Model:
TD127D



BL1811G 1.1Ah

14.4V Li-ion

Battery For Model:
TD126D




BL1411G 1.1Ah

Charger : DC18WA







Charging Time

60 min.



LIGHTER

1.1Ah Lithium-ion Series

Cordless Impact Driver	TD127D / TD126D	
	TD127D 18V Li-ion	TD126D 14.4V Li-ion
<ul style="list-style-type: none">  Variable Speed  Brake  Reversing  Built-in Job Light  Carrying Case 		
	<p>Capacity</p> <p>Machine screw : M4 - M8 (5/32" - 5/16")</p> <p>Standard bolt : M5 - M14 (3/16" - 9/16")</p> <p>High tensile bolt : M5 - M12 (3/16" - 1/2")</p> <p>Coarse thread (in length): 22 - 125mm (7/8" - 4-7/8")</p>	<p>Machine screw : M4 - M8 (5/32" - 5/16")</p> <p>Standard bolt : M5 - M14 (3/16" - 9/16")</p> <p>High tensile bolt : M5 - M12 (3/16" - 1/2")</p> <p>Coarse thread (in length): 22 - 125mm (7/8" - 4-7/8")</p>
<p>Impacts per minute (ipm) 0-3,000</p> <p>No load speed (rpm) 0-2,300</p> <p>Max. fastening torque 140N.m (1,240in.lbs)</p> <p>Dimensions (L x W x H) 173x82x225mm (6-13/16"x3-1/4"x8-7/8")</p> <p>Net Weight* 1.5kg (3.2lbs)</p>	<p>0-3,000</p> <p>0-2,400</p> <p>135N.m (1,200in.lbs)</p> <p>173x82x225mm (6-13/16"x3-1/4"x8-7/8")</p> <p>1.4kg (3.1lbs)</p>	
<p>Standard Equipment : Charger, Battery Cartridge</p>		

*weight according to EPTA-Procedure 01/2003 Items of standard equipment and specifications may vary by country or area.

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN BC-AF